

# Specifications PCS 1

Specifications:	Detail:
Bandwidth and Coding	G.711 3.4 kHz at 56/64 kb/s G.722 7.0 kHz at 48/56/64 kb/s G.722.1 7.0 kHz at 24/32 Kb/s G.723.1 3.4 kHz at 5.3/6.3 kb/s G. 728 3.4 kHz at 16 kb/s G.729 3.4 kHz at 8 kb/s MPEG-4 AAC (mono) 14 kHz at 64/96 Kb/s
Echo Cancellation	Mono

Specifications:	Detail:
Focal Length	F1.8 to 2.9 ( 3.1 to 31mm)
Focus	Auto/Manual
IRIS	Auto
Image Device	1/4 type CCD
Others	Back light Compensation Auto White Balance
Pan Angle/Speed	-100 degree to +100 ( Max 300 degree/s )
Preset Positions	Up to 6 positions
S/N Ratio	50 dB
Tilt Angle/Speed	-25 degree to +25 ( Max 125 degree/s )
Type	Detachable Integrated Camera included
Zoom Ratio	x10 ( Optical Zoom ) x40 ( Digital Zoom )

Specifications:	Detail:
Control Port	RS-232C VISCA ( Mini-DIN 8-pin) for second camera
ITU-T Standards (Excludes audio/video standards)	H.320 H.323 H.221 Bonding H.281 FECC H.225.0 H.239

H.242  
H.243  
H.245  
H.460  
T.120

Lip Synchronization	On/Off
Network Protocols	Telnet ( Server ) HTTP ( Server ) FTP ( Server ) SNMP ( Agent ) DNS ( Client ) DHCP ( Client ) RTP/RTCP TCP/UDP ARP SIP
Security	H.235 Standard AES Password Protected Sony encryption
<b>Specifications:</b>	<b>Detail:</b>
Resolution	XGA 1024 x 768 with PCSA-DSB1S 4CIF 704 x 576 ( H.261 and H.263)
<b>Specifications:</b>	<b>Detail:</b>
Audio Input	Line input x 1 Aux input x 1 External MIC input ( plug in power ) x 2 Internal Microphone x 1
Audio Output	Line output x 1 REC (mixed) output x 1
Data Sharing	Yes (H.239)
Main Unit Dimensions (W x H x D)	10 1/4 x 2 1/4 x 6 3/4 inches ( 258 x 54 x 171 mm)
Main Unit Weight	2 lbs 14 oz ( 1.3 kg )
Memory Stick I/F	Memory Stick Slot x 1
Network	10 Base-T/100 Base-TX
Operating Humidity	30 to 70%
Operating Temperature	41 to 95 F ( 5 to 35 C )
Power Consumption	DC 19.5 V , 3.5A
Power Requirements	AC 120V, 50/60Hz
Remote Commander Unit Dimensions (W x H x D)	2 x 31/32 x 7 1/8 inches ( 50 x 24 x 197 mm )

Remote Commander Unit Weight	5 oz ( 140 g ), incl. batteries
Remote Control	RS-232C x 1
Storage Humidity	25% to 75%
Storage Temperature	-4 to 131 F ( -20 to +55 C )
Video Input	S-Video x 1 Composite x 1
Video Output	S-Video x 2 Composite x 1 RGB x 1
Visca	Mini-DIN 8 pin x 1 for second camera

Specifications:	Detail:
-----------------	---------

Internal MCU	Up to 6 sites
--------------	---------------

Specifications:	Detail:
-----------------	---------

NAT	Yes
QoS (Quality of Service)	Adaptive Rate Control Auto Repeat reQuest IP Precedence DiffServ
UPnP	Yes

Specifications:	Detail:
-----------------	---------

Bit Rate	Up to 2Mb/s Up to 768Kb/s ISDN
Frame Rate	Max 30 fps
Resolution	QCIF (176 x 144) CIF (352 x 288)
Standards	H.261 H.263 H.263+ H.263++ H.264 Interlaced SIF MPEG4 SP@L3

**Call 630-692-2702 or email: [sales@dccil.com](mailto:sales@dccil.com)**



**We provide people solutions!!**